ELETTROPOMPE AUTOADESCANTI
SELF PRIMING ELECTRIC PUMPS
ELECTROPOMPES AUTOAMORÇANTES

GMP PUMPS

G2TMK-A/B 3kW



DESCRIZIONE

Elettropompa autoadescante in bronzo realizzata in versione monoblocco a girante multipalare aperta a rasamento, particolarmente adatta per uso marino e circolazione di acqua di mare.
Corpo, girante e valvola in bronzo, albero in acciaio inox.
La valvola di ritegno posta all'interno della bocca di aspirazione impedisce lo svuotamento della pompa dopo l'arresto garantendone l'adescamento.

DESCRIPTION

Bronze self priming electric pump monobloc execution with multi-blades open impeller, suitable for pumping sea water.
Pump casing, impeller and valve are in bronze; the shaft is in stainless steel.
The check valve located inside the inlet prevents the pump from emptying after it has stopped, guaranteeing its priming.

DESCRIPTION

Electropompe autoamorçantes monobloc en bronze avec turbine ouverte plusieurs pales, indiquée pour d'eau de mer.
Corps, turbine et valve sont en bronze; arbre en acier inox.
Le clapet anti-retour situé à l'intérieur de l'entrée empêche la pompe de se vider après son arrêt, garantissant son amorçage.

CARATTERISTICHE

Altezza massima di aspirazione:	6 m.
Max temperatura del liquido:	+ 70°C
Max passaggio corpi solidi:	8 mm
Portata massima:	24 m³/h
Prevalenza massima:	3,4 bar
Ø aspirazione e mandata:	2"G

FEATURES

Max. suction depth:	*6 m.*
Max. liquid temperature:	*+70°C*
Max. solids diameter:	*8 mm*
Max. delivery:	*24 m³/h*
Max. manometric head:	*3,4 bar*
Ø inlet and outlet:	*2"G*

CARACTERISTIQUES

Hauteur d'aspiration maximale:	*6 m.*
Température Max.:	*+70°C*
Max. diamètre des solides:	*8 mm*
Débit maximum:	*24 m³/h*
Hauteur manométrique:	*3,4 bars*
Ø aspiration et refoulement:	*2"G*

MATERIALI

Corpo pompa:	Bronzo (ASTM B148 C 95800)
Corpo valvola:	Bronzo (ASTM B148 C 95800)
Girante:	Bronzo (ASTM B148 C 95800)
Disco porta tenuta:	Bronzo (ASTM B148 C 95800)
Supporto motore:	Ghisa (EN-GJL-250)
Albero motore:	Acciaio inox Aisi 316 (1.4401)
Tenuta mecc.:	Carbone /Allumina/Nbr/Aisi 316

MATERIALS

Pump body:	*Bronze (ASTM B148 C 95800)*
Valve body:	*Bronze (ASTM B148 C 95800)*
Impeller :	*Bronze (ASTM B148 C 95800)*
Seal disc:	*Bronze (ASTM B148 C 95800)*
Support:	*Cast iron (EN-GJL-250)*
Motor shaft:	*Stainless steel Aisi 316 (1.4401)*
Seal:	*Carbide/Alumina/Nbr/Aisi 316*

MATÉRIAUX

Corps de pompe :	*Bronze (ASTM B148 C 95800)*
Corps valve:	*Bronze (ASTM B148 C 95800)*
Turbine:	*Bronze (ASTM B148 C 95800)*
Couvercle porte Garn. :	*Bronze (ASTM B148 C 95800)*
Support:	*Fonte (EN-GJL-250)*
Arbre moteur:	*Acier Inox Aisi 316 (1.4401)*
Garniture:	*Carbone/Allumine/Nbr/Aisi316*

CARATTERISTICHE MOTORE

Forma costruttiva:	B3/B5
Grandezza:	IEC 90
Classe rendimento:	IE3 (3PH)
Grado di protezione / Classe d'isolamento:	IP55 / F

ENGINE FEATURES

Construction form:	*B3/B5*
Frame:	*IEC 90*
Efficiency class:	*IE3 (3PH)*
Protection / Insulation class:	*IP55 / F*

CARACTÉRISTIQUES DU MOTEUR

Forme constructive:	*B3/B5*
Taillle:	*IEC 90*
Classe de rendement:	*IE3 (3PH)*
Protection / Classe d'isolation:	*IP55 / F*

VERSIONI SPECIALI

Tenute meccaniche materiali diversi
Tensioni speciali / Frequenza 60Hz
SEMI TRASH
Per GASOLIO con tenute in Viton

SPECIAL VERSION

Different mechanical seals
Special voltages / Frequency 60Hz
SEMI TRASH
For GAS OIL with Viton seals

VERSIONS SPECIALES

Garnitures mécaniques différentes
Voltages spéciaux / Fréquence 60Hz
SEMI TRASH
Pour GAS-OIL avec garniture en Viton

DATI TECNICI

TECHNICAL DATA

DONNES TECHNIQUES

Tipo *Type*	**P2** (kW)	**Tensione** *Voltage Tension* (Volt)	**Freq.** (Hz)	**Corrente nominale** *Rated current Intensité* **(A)**	**Protezione** *Protection Protection*	**Giri/min** *RPM Tours/min*	**Cond.** **(µF)**	**Peso** *Weight Poids* **(Kg.)**	**Dimensioni** *Dimensions* **AxBxC (mm)**	**Imballo** *Packaging Emballage*
G2TMK-A/B T.	3	230/400		12 / 7	IP 55	2900	-	50	400x600	

ELETTROPOMPE AUTOADESCANTI
SELF PRIMING ELECTRIC PUMPS
ELECTROPOMPES AUTOAMORÇANTES

G2TMK-A/B 3kW

CURVE DI PRESTAZIONE

Tolleranze e curve secondo UNI EN ISO 9906
Appendice A

PERFORMANCES CURVES

Tolerances and curves according to UNI EN ISO 9906
Attachment A

COURBES DE PERFORMANCES

Tolérance et courbes conformes aux normes UNI EN ISO 9906
Annexe A



DIMENSIONI

DIMENSIONS

DIMENSIONS



La GMP si riserva la facoltà di modificare senza preavviso i dati riportati in questo catalogo – *GMP can alter without notifications the data mentioned in this catalogne. – GMP se riserve le droit de modifier sans préavis les données techniques dans ce catalogne.*